# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| | | | |
|---|---|---|---|
| **Supplier's name or trade mark:**  UMAGE | | | |
| **Supplier's address:**  UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK | | | |
| **Model identifier:**  2560 (light-source) | | | |
| **Type of light source:** | | | |
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | LED strip | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with specific dimmers |
| **Product parameters** | | | |
| Parameter | Value | Parameter | Value |
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 24 | Energy efficiency class | E |
| Useful luminous flux ($\phi$use), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 3 322 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 400 or 2 700 or 3 000 |
| On-mode power ($P_{on}$), expressed in W | 23,6 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 92 |
| Outer dimensions without separate control gear, light- | Height | 8 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| | Width | 1 340 | | |
| | Depth | 1 | | |

| | | | |
|---|---|---|---|
| ing control parts and non-lighting control parts, if any (millimetre) | | | |
| Claim of equivalent power[a] | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,438<br>0,401 |
| **Parameters for LED and OLED light sources:** | | | |
| R9 colour rendering index value | 62 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |

[a]'-' : not applicable;

[b]'-' : not applicable;

Spectrum     1.0 = 5.927e+001mW/nm

Wavelength(nm)