

Nimba

60 / 90 / 120 / 180


Antoni Arola, 1997
Hanging lamps

Nimba 60




A

Nimba 90




B

Nimba 120



C

Nimba 180



D



A floating ring comprising a metal profile and an inner shade that scatters the light. The lamp's name is inspired by 'the nimbus or halo around holy images, which can be seen, but is not there'.

Nimba shines light on the centre of nowhere to radiate out in all directions, effortlessly combining simplicity and high technology.

LED versatility has enabled two new sizes, one smaller and one larger (60 and 180 cm diameter), to highlight all types of space and project with extensive, serene and soft light radiation.

GENERAL DESCRIPTION

Structure available in 2 finishes: stainless steel or golden.

White engineering plastic lampshade.

Black metallic circular ceiling plate with power supply incorporated.

Electric cable length: 5 m / 196.8".

LIGHT SOURCE

(A)

Strip of 144 LEDs
Power system: 45 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 85
Lifetime: 40.000 h
Luminous flux: 1.798 lm

(B)

Strip of 192 LEDs
Power system: 65 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 85
Lifetime: 40.000 h
Luminous flux: 2.540 lm

(C)

Strip of 276 LEDs
Power system: 95 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 85
Lifetime: 40.000 h
Luminous flux: 3.713 lm

(D)

Strip of 408 LEDs
Power system: 140 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 85
Lifetime: 40.000 h
Luminous flux: 5.550 lm

Built-in LED.
Energy efficiency class (E.E.C): A⁺⁺... A
Suitable for adjustment 1-10V (external dimmer switch 1-10V not included).
Fixture suitable only for indoor use.
Always use this light source.

Input voltage: 90 ~ 305* VAC
(50 Hz / 60 Hz) According to destination.

* UL Market: They have been tested with UL certification with an input voltage (VAC) of 120 V and 277 V. Han sido testadas con la certificación UL con una tensión de entrada (VAC) de 120 V y 277 V.



APPROXIMATE WEIGHT (unpacked)

- (A) Nimba 60: 7 Kg / 15.4 lb
- (B) Nimba 90: 9 Kg / 19.8 lb
- (C) Nimba 120: 12 Kg / 26.5 lb
- (D) Nimba 180: 16 Kg / 35.2 lb

REGULATIONS

CE



IP 20

UNE-EN 60598

UNE-EN 55015

UNE-EN 62031

UNE-EN 61000-3-2

UNE-EN 60529

UNE-EN 61347-2-13



Class 2

Dry location only

UL-1598

UL-8750

E-336377

MAINTENANCE

Clean with a smooth cloth. Do not use ammonia, solvent or abrasive cleaning products.

OTHERS

The lamp is delivered in different packages.
The assembly instructions are delivered with the product.

MODELS

